

# Traditional Series Analog Clocks



## POE / IP Clocks

It's never been easier to synchronize the time throughout your facility. OneVue Clocks are delivered preconfigured, ready to quickly access your existing network. Simply take the clocks out of the box, connect to PoE power (Power over Ethernet), and hang them on the wall. The clocks will immediately access your network and synchronize perfectly to keep your organization running on time, even through power outages or Daylight Saving Time shifts.

### Traditional Series Analog Clocks

Easy-to-read dials and durable thermoplastic frames and lenses make our Traditional Series Analog Clocks ideal for almost any setting. Available in a variety of colors, sizes, and dial options including custom dials to showcase your facility name or logo.



12.5" or 16"  
Traditional Series



12.5" or 16"  
Traditional Series  
General 12/24



Easy-to-assemble bracket kit lets you create a dual-sided clock for hallways or other large areas.

#### POE TRADITIONAL SERIES ANALOG CLOCKS

PART NO.	DESCRIPTION
162-PE110A01	12.5" (31.75cm) Black , PoE, Configured
162-PE110A05	12.5" (31.75cm) Black, General 12/24 Dial, PoE, Configured
162-PE110W01	12.5" (31.75cm) White, PoE, Configured
162-PE150A01	16" (40.64cm) Black, PoE, Configured
162-PE150A05	16" (40.64cm) Black, 12/24 General Dial, PoE, Configured

### Dual Clock Kit

Create an easy-to-read dual-sided clock for hallways or other large areas with our Dual Clock Kit. The kit includes a bracket, mounting plate, and hardware to easily assemble and install two 12.5" (31.75cm) Traditional Series Clocks back-to-back.

#### DUAL CLOCK KIT

PART NO.	DESCRIPTION
199-000040	12.5" (31.75cm) Dual Mounting Kit
199-000041	12.5" (31.75cm) Dual Mounting Kit - White



## FEATURES

- Automatically adjusts for Daylight Saving Time
- Clock Lock feature can be used to securely mount to the wall
- Clock configuration to access your network is accomplished online prior to delivery for plug-and-play convenience

---

### TRADITIONAL SERIES SPECIFICATIONS

- Durable thermoplastic frames and lenses
- 12.5" (31.75cm) or 16" (40.64cm) diameter
- Clock depth: 2.5" (6.4cm)
- Clock power: PoE 802.3 at/af compatible
- Operating range: 32° - 158°F (0° - 70°C)

---

### DIALS

- Customized clock faces are available to display your organization's name or logo
- Please call for more information

To Learn More:  
Call - 855-602-2934  
Email - [info@primexinc.com](mailto:info@primexinc.com)  
[primexinc.com](http://primexinc.com)



©2022 by Primex, Inc.  
The Primex logo is a registered trademark of Primex, Inc. All Rights Reserved. 4.4.22